



Safety Devices

Due to Health & Safety Regulations all doors with auto open & close require Safety Bottom Edges & Photo Cells as Standard. If the door closes on an obstruction it will automatically stop & close.

Folding Shutter Doors.

Fully Glazed folding doors designed for wide openings with limited headroom. Each door is custom manufactured to suit most types of structural openings. A concrete or steelwork lintel is required to support the sliding door track.

Door Leaves

Formed from cold rolled Galvanised Steel with Glazing Rails. Insulated Polycarbonate Glass panels, fully weather sealed. Block windows assembled during installation of the door. The Glass parts give maximum natural lighting to the inside of the building in more common areas such as Train Stations, Stations & Offices.

Frame Profile

Formed from cold rolled galvanised steel, profile with "L" section and internal frame structure "T" section.

Top Track

Galvanised steel, finished Black as Standard.

Electric Operation (optional extra)


3 phase, 415Volt motor with integral gearbox mounted on the top track or to the side of the door (dependant on conditions & sideroom availability). Electrical equipment includes a reversing on line starter with push buttons marked 'open', 'close' and 'stop'. Isolator by Client. Wiring is not included unless otherwise requested. Special motors and starters are available to suit individual requirements.

Finish


Polyester Powder Coated to standard RAL colour to both internal & external face of the door.



Section Through Floor Detail



Section Through Head Detail



Northern Doors (UK) Ltd



NORTHERN DOORS (UK) LTD

Kingsforth Road, Thurcroft,

Rotherham, S66 9HU

+441709 545999

mail@northerndoors.co.uk